

AVL TECHNOLOGIES

MODEL 2012K GLOBAL

2.0 METER MOTORIZED VEHICULAR SNG ANTENNA

Reflector	2.0 meter AvL Carbon-Fiber
Feed	Mode-Matched Horn
Optics	Offset, Prime Focus, .8 F/D
Az/EI Drive System	Patented Roto-Lok® Positioner
Mount Geometry	Elevation over Azimuth
Polarization Adjustment	Rotation of Feed



Electrical RF

Receive

Transmit

Frequency	10.95-12.75 GHz	13.75-14.5 GHz
Gain (Midband)		
2-port	45.7 dBi	47.5 dBi
4-port	45.5 dBi	47.3 dBi
VSWR	1.30:1	1.30:1
Beamwidth (degrees)		
-3 dB	.86	.72
-10 dB	1.65	1.40
First Sidelobe Level (Typical)	-22 dB	-22 dB
Radiation Pattern Compliance	>3 dB better than FCC §25.209, ITU-R S.528.5	
Antenna Noise Temperature	47° K at 30° Elevation	
Polarization	Orthogonal standard, Optional Co-pol	
Power Handling Capability	0.5KW per port	
Cross-Pol Isolation		
On-Axis (minimum)	35 dB	35 dB
Off-Axis (within 1 dB BW)	25 dB	35 dB
Off-Axis (peak)	20 dB	30 dB
Feed Port Isolation – TX to RX	75 dB	
Satellite system Compliance	FCC, PanAmSat, Intelsat, Eutelsat, AsiaSat	

Controllers

Standard	Three-axis Jog Control & Display with Auto-stow
Optional Upgrades	
Semi-automatic Operation	Drive to calculated position based on operator entered vehicle location, heading, plus satellite (longitude or listed)
Automatic Operation	Drive to calculated position based on auto GPS and Flux-Gate Compass data and satellite peaking with LNB signal
Size	Two Rack Units for Semi-automatic & Automatic Controllers
Input Power	110/240 VAC, 1 ph, 50/60 Hz, 15 amps peak

AVL TECHNOLOGIES

MODEL 2012K GLOBAL 2.0 METER MOTORIZED VEHICULAR SNG ANTENNA

Mechanical

Az/EI Drive System	Patented Roto-Lok® Cable Drive System
Polarization Drive System	Non Back-driving Worm Gear
Travel	
Azimuth	270° Standard, 400° Optional for 2-port or Feed Boom Mounted HPA
Elevation	True elevation readout from calibrated inclinometer
Mechanical	0° to 90° of Reflector Boresight
Electrical	Standard limits at 5° to 65° (CE Approval) or 5° to 90°
Polarization	±95° for 2-port and 3-port Feeds ±50° for 2-port Wideband and 4-port feeds
Speed	
Slewing/Deploying	2°/second
Peaking	0.2°/second
Motors	24V DC Variable Speed, Constant Torque
RF Interface	
HPA Mounting	Feed Boom, Rear of Reflector or Inside Truck
Axis Transition	Twist-Flex or Rotary Joints
Waveguide	WR 75 Cover Flange at Interface Point
Coax	RG59 run from feed to base plus 25 ft. (8 m)
Electrical Interface	25 ft. (8 m) Cable with Connectors for Controller
Manual Drive	Handcrank on Az and EI Axii, Leads from 12VDC Pol Motor
Weight	300 lbs. (136 kg)
Stowed Dimensions	103½ L x 80 W x 20 H inches (263 L x 203 W x 51 H cm)

Environmental

Wind	
Survival	
Deployed	60 mph (121 kmph)
Stowed	100 mph (161 kmph)
Operational	45 mph (72 kmph), Gusts to 60 mph (97 kmph)
Pointing Loss in Wind	
20 mph (32 kmph)	0.20 dB Typical
30 Gusting to 45 mph (48 to 72 kmph)	1.0 dB Typical
Temperature	
Operational	+5° to 125°F (-15° to 52° C)
Survival	-40° to 140°F (-40° to 60° C)